



TITANFLEX

TELEPHONE: (414) 263-2770
800-227-5220
FAX: (414) 562-2710
800-424-6330



LIQUID WASTE

SWC509 Ultravac Oilfield Vacuum Hose

Designed for medium to heavy duty vacuum service. Ideal for diluted industrial chemicals and oil field waste pit recovery service for drilling mud, sludge, slurries, sediments with diesel, crude oil, salt, fresh water and tank bottoms. Unique kinkless design. Ultra-flexible design provides extreme bend radius in all sizes. Lightweight, easy to lift, drag and move around. Heavy duty design allows higher working pressures.

Tube: Specially compounded Nitrile.

Reinforcement: Multiple plies of polyester yarn w/ dual wire helix.

Cover: Corrugated SBR (Abrasion, outdoor & ozone resistant).

Temperature Rating: -40° to +160° F.



PETROLEUM

SWC609 TITANFLEX Petroleum Corrugated Petroleum Hose

TITANFLEX Petroleum® is designed for petroleum suction and discharge applications where full vacuum, higher working pressures, extreme flexibility and easier handling are required. TITANFLEX® hose products incorporate superior performance characteristics with advanced flexing abilities and lightweight construction. TITANFLEX® products are clearly unmatched in the industry.

Tube: Seamless high grade Nitrile (60% aromatics, Class A RMA)

Reinforcement: Multiple plies of polyester yarn with wire helix

Cover: Corrugated specially compounded Nitrile

Temperature Rating: -40°F to +180°F

I.D.	O.D.	Bend Radius	Working PSI	Wt. LB/FT SWC509	Wt. LB/FT SWC609	Vacuum	SWC509 List per foot	SWC609 List per foot
1"	1-1/2"	1"	250	.48	N/A	Full	\$ 6.63	N/A
1-1/2"	2-1/16"	1-1/2"	250	.72	.72	Full	\$ 7.68	\$ 9.01
2"	2-9/16"	2"	250	.93	.92	Full	\$ 8.47	\$ 10.28
2-1/2"	3-1/8"	2-1/2"	250	1.40	1.35	Full	\$ 10.21	\$ 12.84
3"	3-5/8"	3"	250	1.66	1.66	Full	\$ 11.50	\$ 14.69
4"	4-5/8"	4"	150	2.23	2.26	Full	\$ 15.01	\$ 21.05
6"	6-3/4"	10/8"	125	4.02	4.10	Full	\$ 29.96	\$ 46.27