

# PRODUCT INFORMATION BULLETIN

## SERIES SUPER-FLEX® FL-7 FUEL LINE HOSE CARB 2006 S.O.R.E. (Small Off-Road Engines) Approved per Executive Order Q-08-013, EPA 2009 Compliant, meets or exceeds SAE J30R7, SAEJ30R14T2

Parker Hannifin's Industrial Hose Division is pleased to introduce our new flexible *Super-Flex FL-7* fuel line hose. The *FL-7* hose is extremely flexible, which is required for routing purposes on small engines. This product includes an abrasion and weather resistant cover that helps protect it from external application abuse. This new hose surpasses all of the CARB (California Air Resource Board) and EPA stringent permeation requirements of 15g/m<sup>2</sup>/day. It also meets or exceeds SAE J30R7 and SAE J30R14T2 specifications.

**Approved for biodiesel fuels up to 20% (B20) and 85% ethanol (E85) fuel**

Design Factor: 5:1

<b>Tube</b>	Nitrile with a THV Barrier
<b>Cover</b>	Black Hypalon
<b>Reinforcement</b>	Multiple Aramid Plies
<b>Temperature Range</b>	-40°F to + 257 °F (-40°C to +125°C)
<b>Branding</b>	PARKER 38904 SUPER-FLEX® FL-7 1/4" ID SAE J30R7/R14T2 FUEL LINE 9PKHPLINE389 EPA COMPLIANT 15 g/m <sup>2</sup> /day CARB Q-08-013 MAX WP 50 PSI USA 071808A
<b>Brand Description</b>	White Ink
<b>Compare to</b>	Avon Greenbar 700, Gates 4219B

Part Number	ID (mm)	Reinf Plies	OD (mm)	App Wt/100 ft (lbs)	Min Bend Rad (in)	Max WP (psi)	Std Pack Qty	Stock (Y) Or MOQ	List Price
38903	3/16 (4.8)	2	0.406 (10.3)	63	1.25	50	250	Y	\$2.63
38904	1/4 (6.4)	2	0.500 (12.7)	92	1.50	50	250	Y	\$2.84
38905	5/16 (7.9)	2	0.562 (14.3)	108	2.00	50	250	Y	\$3.16
38906	3/8 (9.8)	2	0.625 (15.8)	123	2.50	50	250	Y	\$3.68
38908	1/2 (12.7)	2	0.781 (19.8)	176	4.00	50	250	5,000	\$5.26

**Packaging:** Plastic reels, nominal 250 ft., maximum 3 pieces, no piece shorter than 25 ft.

If there are any questions please contact our Customer Service toll-free at: (800) 227-5220.



General Rubber Company  
 16988 West Victor Road  
 New Berlin, WI 53151  
 Telephone: (262) 754-5522  
 Fax: (262) 754-5525

**Parker Hannifin Corporation**  
 17295 Foltz Industrial Pkwy  
 Strongsville, OH 44149  
 Telephone: (440) 268-2120  
 Fax: (440) 268-2230